

Accelerometer KS901MF

for Vibration Analysis



Accelerometer KS901MF

The lightweight uniaxial piezoelectric accelerometer has been designed for analyzing the vibrations of devices with slight to medium excursions. With a weight of 24 g it is mounted to the device under test (DUT) via the built-in magnet.

Properties

- Uniaxial precision accelerometer with compression ceramic
- Vibration analysis over a wide amplitude & frequency range
- ICP® output allows long cables under harsh EMI conditions
- Sturdy stainless steel housing
- Mounting via build-in magnet

Specifications

Design	Piezo compression ceramic
Power supply	ICP®, 2 to 20 mA
Sensitivity	typ. 100 mV/g ±20% @ 80 Hz
Residual noise	0.4 µg
Linear frequency range	0.2 Hz to 10 kHz (±3 dB)
Measurement range	±60 g _{pk}
Temperature range	-10 to +100 °C (14 to 212° F)
Case	D x L = 12 x 39 mm, stainless steel
Weight (sensor only)	24 g (0.85 oz)
Protection grade	IP60
Mounting	built-in magnet head
Magnet force	45 N
Cable	L = 3 m, with BNC connector
Order information	<ul style="list-style-type: none"> • Accelerometer KS901MF NTi Audio # 600 010 347 • ICP® Adapter ASD for operation with XL2 NTi Audio # 600 010 223

All data are subject to change without notice.
ICP® is a registered trademark of PCB Piezotronics.